



Inch sizes available

1		2		3													
l <sub>1</sub>	d <sub>1</sub>	l <sub>2</sub>		d <sub>3</sub>	d <sub>4</sub>	h <sub>1</sub>	h <sub>2</sub>	h <sub>3</sub>	h <sub>4</sub> Stroke								
22	M 3	-	6	8	10	12	16	-	-	-	8	10,5	18,5	2	23	3	
22	M 4	M 5	12	16	20	25	32	-	-	-	8	10,5	18,5	2	23	3	
30	M 3	-	6	8	10	12	16	-	-	-	10	13	24,5	4	31	3,5	
30	M 4	-	12	16	20	25	32	-	-	-	10	13	24,5	4	31	3,5	
30	M 5	M 6	12	16	20	25	32	40	50	-	10	13	24,5	4	31	3,5	
45	M 4	-	12	16	20	25	32	-	-	-	10	13	24,5	4	34	3,5	
45	M 5	M 6	12	16	20	25	32	40	50	-	10	13	24,5	4	34	3,5	
63	M 6	M 8	12	16	20	25	32	40	50	63	13,5	17,5	31	6,5	45	4	
63	M 10	-	20	25	32	40	50	63	80	-	13,5	17,5	31	6,5	45	4	
78	M 8	M 10	16	20	25	32	40	50	63	80	16	21	36	8	54	4	
78	M 12	-	20	25	32	40	50	63	80	-	16	21	36	8	54	4	
92	M 10	M 12	16	20	25	32	40	50	63	80	19	24	43	11	64	4	
92	M 16	-	25	32	40	50	63	80	-	-	19	24	43	11	64	4	
108	M 12	M 16	25	32	40	50	63	80	120	-	23	30	50,5	12	75	5	

**Specification**

- Handle  
Zinc die casting
- Plastic coated  
black, RAL 9005, textured finish  
black, RAL 9011, silk finish  
orange, RAL 2004, textured finish  
red, RAL 3000, textured finish  
silver, RAL 9006, textured finish
- chrome-plated
- uncoated  
slide grinded
- Threaded stud and retaining screw  
Steel  
- Tensile strength class 5.8  
- blackened
- Strength values of screws → Page 1481
- RoHS

- SW
- SZ
- OS
- RS
- SR
- CR
- RH

**Information**

Adjustable hand levers GN 300 are ideal whenever parts have to be clamped in a confined space or in a particular lever position. The centre insert is connected to the lever via serrations which can easily be disengaged.

Pulling the lever, disengages the serrations and allowing it to be swivelled to the ideal clamping position. On releasing the lever the serrations automatically re-engage.

see also...

- Adjustable hand levers GN 300.1 (threaded stud Stainless Steel) → Page 323
- Adjustable Stainless Steel-Hand levers GN 300.5 → Page 325
- Flat adjustable hand levers GN 302 → Page 335
- Adjustable hand levers GN 300.4 (increased clamping force) → Page 333
- Adjustable hand levers GN 303 (with push button) → Page 329

How to order

**GN 300-63-M8-25-SW**

1	l <sub>1</sub>
2	d <sub>1</sub>
3	l <sub>2</sub>
4	Color (Finish)